


AcoustiSorb®

Soundproofing & noise absorption



Features:



Description:

ModularWalls' proprietary AcoustiSorb Panel is designed and manufactured in Australia. It is a simple, effective and aesthetically pleasing acoustic wall panel with both noise absorption and sound reduction properties.

AcoustiSorb is suitable for both external and internal applications. Its lightweight and robust design makes it an ideal noise control solution for noise-intensive environments. Additionally, its acoustic performance can be tuned by customising the core materials.

Product Specification:

Panel Lengths 2400 / 3000 / 4000mm

Panel Heights 600mm

Panel Thickness 75 / 100mm

Moisture Absorption

Exposure to an atmosphere of 50°C & 95% RH for four days gives moisture absorption of less than

0.2% by volume

Fire Resistance ¹ (AS 1530.3)

Ignitability: 0

Spread of Flame: 0 Heat Evolved: 0

Smoke Developed: 0-1

Acoustic Performance:

Materials	75mm 100mm	
Density ²	8 kg/m ²	9.2 kg/m ²
Rw³	25 dB	27 dB
NRC	0.9	0.95

	Absorption Coefficient			
Freq. (Hz)	250	500	1000	2000
75mm	0.6	1.0	1.0	0.95
100mm	0.8	1.0	1.0	1.0

Product Applications:

- · Road & Rail Corridors
- Loading Docks
- Dyno Rooms
- Acoustic Enclosures (Pool Pumps, HVAC, Generators)
- Drive-throughs
- · Cinemas and Theatres
- Water Parks
- Pubs and Clubs
- Restaurants

Commercial Warranty:

Product 10 years warranty ⁴

Design Life 50+ years

Finish Type Powder Coated

Colour Surfmist

(Custom colours are available upon request.)



^{2.} Surface density of 100mm panel can be tuned to 16.5 kg/m².



^{3.} Rw of 100mm panel can be tuned to 30 dB.

^{4.} Terms and Conditions apply.